





Bright White (958)





Valmex[®] Car Park Plus[™] has been developed exclusively by Mehler for the commercial car park market in Australia. Meeting all the technical requirements of the majority of retail clients, with an impressive 300cm width and backed by a 15-year warranty, designed to perform in rugged Australian conditions.

Material Composition		
Finish	Multi-composed top coating lacquering with titanium dioxide (TIO2) reinforcement and highly concentrated PVDF mixture on both sides, weldable without grinding.	
Base Fabric	DIN ISO 2076	Polyester Plain Weave L1/1
Yarn Count	DIN ISO 2060	dtex 1100
Low Wick Treatment	Methylene Blue Liquid Method	mm <5
Total Weight	EN ISO 2286-2	750gsm
CMD Ratio (Front/Back)	3:2	
Mechanical Properties		
Tensile Strength (N/5cm)	DIN EN ISO 1421 V1	Warp 3290 Weft 3350
Tear Strength (N)	DIN 53363	Warp 409 Weft 333
Adhesion (N/5cm)	PA 09.03	100N
Cold Resistance	DIN EN 1876 -1	- 40c
Heat Resistance	PA 07.04	+70c
Roll Width	300cm	
Roll Length	100m	







Easy Maintenance



Tear Resistance

UV Resistance



*Anti Wicking



WARRANTY

